



# RoadCharm

## BRP472 LED 210/NW 163W 220-240V DME

21000 lm - 163 W - 4000 K

Developed with the aim to become your long term partner ,the system ready architecture of RoadCharm enables you to enjoy the benefits of connected lighting systems today and also gets the city ready for the innovations to come. ;It is designed to achieve better light uniformity and a maximum spacing between poles for both pedestrian and vehicle road applications. With its die-cast aluminium housing and Philips LED platform, it is easy to maintain, has a long lifetime and a consistency you can count on. It also offers two housing sizes and a range of beam optics to fully cater to different road configurations and conditions. ;RoadCharm offers 50% energy savings compared to conventional lamp systems, making it the perfect sustainable lighting solution for any emerging metropolis.

### Product data

General Information		Serviceability class	
Lamp colour code	740 neutral white	Class B, the luminaire is equipped with some serviceable parts (when applicable): driver, control units, surge-protection device, front cover and mechanical parts	
Light source replaceable	No	Light Technical	
Driver included	Yes	Standard tilt angle post-top	-
Optical cover/lens type	PC-MLO [ Polycarbonate micro lens optic]	Operating and Electrical	
Control interface	-	Input Voltage	220 to 240 V
Connection	Mains outlet socket	Input frequency	50 or 60 Hz
Cable	-	Power factor (min.)	0.9
Protection class IEC	Safety class I (I)		
Flammability mark	F [ For mounting on normally flammable surfaces]		
CE mark	CE mark		
ENEC mark	-		
Constant light output	No		
Light source engine type	LED		

## Controls and Dimming

Dimmable	No
----------	----

## Mechanical and Housing

Housing material	Aluminum die-cast
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Mounting device	48/60S [ Side-entry for diameter 48-60 mm]
Optical cover/lens shape	Ball, globular
Optical cover/lens finish	Clear
Overall length	1012 mm
Overall width	364 mm
Overall height	115 mm
Effective projected area	0.32 m <sup>2</sup>
Colour	Grey

## Approval and Application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]
Surge protection (common/differential)	Luminaire surge protection level up to 15 kV differential mode and 15 kV common mode

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	21000 lm
-------------------------------------	----------

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	130 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>70
Initial chromaticity	(0.38, 0.38) SDCM < 5
Initial input power	163 W
Power consumption tolerance	+/-10%

## Application Conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product Data

Full product code	911401661305
Order product name	BRP472 LED 210/NW 163W 220-240V DME
Order code	911401661305
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401661305
SAP net weight (piece)	13.799 kg



## Dimensional drawing



BRP472 LED 210/NW 163W 220-240V DME

