



MSR

MSR 575/2 10H 1CT/4

MSR – bright vivid colours, always The high colour rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colours of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical	
Cap base	GX9.5 [GX9.5]	Lamp Luminous Efficacy EM (Min)	75 lm/W
Burning Position	UNIVERSAL [Any/Universal]	Lamp Luminous Efficacy EM (Nom)	83 lm/W
Main application	Studio/Disco	Colour Rendering Index,horiz (Nom)	70
Life to 50% failures (nom.)	1000 h	Power (Rated) (Nom)	575 W
System description	Cold Strike	Lamp current (nom.)	6.75 A
Colour Code	2	Ignition supply voltage (min.)	207 V
Lamp Luminous Flux 25°C EL (Min)	42750 lm	Dimmable	No
Lamp Luminous Flux 25°C EL (Nom)	47500 lm		
Chromaticity coordinate X (nom.)	302		
Chromaticity coordinate Y (nom.)	320		
Colour Temperature, horizontal (Nom)	6990 K		

MSR

Mechanical and Housing

Cap-base information 20mm (20)

Luminaire Design Requirements

Bulb temperature (max.) 700 °C

Pinch temperature (max.) 350 °C

Product Data

Full product code 871829122127200

Order product name MSR 575/2 10H 1CT/4

EAN/UPC – product 8718291221272

Order code 928171605115

SAP numerator – quantity per pack 1

Numerator – packs per outer box 4

SAP material 928171605115

SAP net weight (piece) 0.057 kg

Dimensional drawing

2

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 575/2	30 mm	7.0	64 mm	66 mm	65	125 mm	36 mm	35	34 mm
10H 1CT/4		mm			mm			mm	

MSR 575/2 10H

Photometric data

