



SportsStar-BVP621/BVP622/ EVP622

BVP622 LED922/857 900W S7 9007 GC 5C O

Philips SportsStar LED Floodlight sets the standard in high quality optical distribution with high performance and low light pollution (or effective light control). From Sports to Area Lighting, our system, including the high masts needed, projects the light exactly where it should be going. Choose the right illumination levels for any given setting with Philips SportsStar LED Floodlight.

Product data

General Information	
Lamp colour code	857 daylight
Light source replaceable	No
Driver included	No
Optical cover/lens type	PC-MLO [Polycarbonate micro lens optic]
Control interface	-
Connection	CU5 [Connection unit 5-pole]
Cable	Cable 1.5 m with plug
Protection class IEC	Safety class I (I)
Flammability mark	NO [-]
CE mark	-
Light source engine type	LED
Serviceability class	Class B, the luminaire is equipped with some
	serviceable parts (when applicable): driver,
	control units, surge-protection device, front
	cover and mechanical parts

Light Technical	
Standard tilt angle post-top	-
Standard tilt angle side entry	-
Operating and Electrical	
Input Voltage	- V
Input frequency	- Hz
Power factor (min.)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing material	Aluminium
Optical cover/lens material	Polycarbonate
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens finish	Frosted

Datasheet, 2020, March 19 data subject to change


SportsStar-BVP621/BVP622/EVP622

Overall length	680 mm	
Overall width	730 mm	
Overall height	307 mm	
Colour	Aluminium	
Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Surge protection (common/differential) -		
Initial Performance (IEC Compliant)		
Initial luminous flux	92200 lm	
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	102.44 lm/W	
Lamp colour temperature	5700 K	
Colour Rendering Index	>80	
Initial input power	900 W	

Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	911401594251
Order product name	BVP622 LED922/857 900W S7 9007 GC 5C O
Order code	911401594251
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12 NC)	911401594251
Net Weight (Piece)	21.999 kg



Dimensional drawing



BVP621/BVP622/EVP622 SportsStar



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.